



WIRELESS SMOKE DETECTOR Model 216 & 217

AMAC's monitored smoke detector provides an extra level of protection for your residents and community. The supervised, wireless detector is battery powered allowing quick installation and easy maintenance. When activated by a smoke or heat condition, the smoke detector alarm sounds and triggers the console unit to send a distinct signal to the monitoring station. Staff will be immediately notified of the condition allowing appropriate, timely response. Additionally, the smoke detector battery is monitored and will transmit a signal to the monitoring station when the battery is low.

MODEL	216	217
FREQUENCY	303.875 MHz	433 MHz
CONSOLE UNIT COMPATIBILITY	Model 800, 850 1000 and 1100	Model 833, 850XL 900 and 1100
DIMENSIONS	5.3" (135 mm) dia.	2.3" (58mm) ht
WEIGHT	8.5oz. (241g) without battery	
POWER SOURCE	One 3 Volt CR123A Lithium Battery(incl.) Replace w/Duracell DL123A or Panasonic CR123A.	
SENSOR	Photoelectric	
AGENCY LISTINGS	UL 217 – Standard for Single and Multiple Station Smoke Alarms	

www.amac.com

Distribution Partner

American Medical Alert Corp.
3265 Lawson Blvd.
Oceanside, New York 11572
(800) 286-2622 Fax: 516-536-5276